

SC-RR-67-616
C.5


SC-RR-67-616

TID-4500

NUCLEAR EXPLOSIONS - PEACEFUL
APPLICATIONS

HEALTH AND SAFETY

September 1967



MAXIMUM MISSILE RANGES FROM
SURFACE AND BURIED EXPLOSIONS

DISTRIBUTION STATEMENT A

Approved for Public Release

Distribution Unlimited

L. J. Vortman, 7111

Reproduced From
Best Available Copy

20011026 084

SANDIA LABORATORIES



Issued by Sandia Corporation,
a prime contractor to the
United States Atomic Energy Commission

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

Printed in the United States of America
Available from
Clearinghouse for Federal Scientific and Technical Information
National Bureau of Standards, U. S. Department of Commerce
Springfield, Virginia 22151
Price: Printed Copy \$3.00; Microfiche \$0.65

TID-4500 (50th Ed.)
(UC-41, UC-35)
Nuclear Explosions -
Peaceful Applications
Health and Safety

SC-RR-67-616

MAXIMUM MISSILE RANGES FROM
SURFACE AND BURIED EXPLOSIONS

L. J. Vortman, 7111
Sandia Laboratory, Albuquerque

September 1967

ABSTRACT

The ballistic boundaries, or maximum ranges of ejected material, for many applicable surface and buried explosions are summarized and scaling expressions are derived which will be helpful in predicting the ballistic boundaries for explosions of other energies. In establishing safety zones it is advisable to multiply predicted boundaries by a factor of 1.5 to 2.0, because of a finite probability that the boundaries observed for a limited number of events will be exceeded if more shots are fired.

TABLE OF CONTENTS

| | <u>Page</u> |
|---------------------------------|-------------|
| Theory | 6 |
| Results of Experiment | 7 |
| Surface Bursts | 7 |
| Buried Charges | 8 |
| Conclusions | 9 |
| References | 14 |

MAXIMUM MISSILE RANGES FROM SURFACE AND BURIED EXPLOSIONS

An estimate of maximum missile distances is needed for establishing safety criteria for cratering explosions. Ejecta formation and distribution involves complex mechanisms as indicated by the following outline:

Ground Shock:

- Initial velocity (particle velocity of the shock wave)
- Initial angle (position in the shock field)
- Missile size
 - Medium strength properties
 - Pre-existing fracture patterns
 - Shock strength

Modifying Phenomena:

- Acceleration due to gas expansion
- Acceleration by gas flow or air flow
- Acceleration or deceleration by friction with adjacent material
- Acceleration or deceleration and direction change by ballistic collision
- Deceleration by drag
- Local wind velocity (for small particles)

Theory

No general theory of ejecta formation and distribution exists. While Cherry (Reference 1) has a code which partially shows the dispersion for certain buried explosions, it neglects missile size and all of the modifying phenomena.

Sherwood (Reference 2) has treated air drag by adopting a ballistic trajectory after the acceleration due to gas expansion has ceased. He also adopts an experimentally obtained particle-size distribution. He does not take into account this particle-size spatial distribution within the stress field: the smallest particles originate closest to the charge where stress levels are high and where at certain locations initial velocities are high. Still, his work is a considerable refinement on that of Cherry, and of Hess and Nordyke (Reference 3).

Any further development of Sherwood's approach would be better suited to determining ejecta distribution than to defining a ballistic boundary. The maximum missile range is a probabilistic matter relating to medium properties and the particle-size spatial distribution mentioned above. Using Sherwood's model, it is possible to determine the maximum range for any given particle size; it is not possible to determine the probability that a missile of a size which maximizes range will also originate from a point which maximizes range.

Bishop (Reference 4) treated the simpler situation of the ballistic boundary from cased explosive charges detonated above ground, based on early work by Gurney (Reference 5). Their methods if applied to surface bursts or buried uncased charges would result in overestimates of maximum missile ranges.

Absence of a theory for predicting a ballistic boundary makes it necessary to fall back on experimental determination of that boundary.

Results of Experiment

Tables I-IV summarize the available data on ballistic boundaries without regard for missile size. The tables cover the boundaries for missiles from spherical charges on and in soil and rock, and for hemispherical charges on soil and rock. It should be emphasized that the ranges given were the maximums observed, but it is quite possible that missiles at greater ranges escaped detection. Consequently maximum range in the sense used here should be interpreted as meaning "at least as far as."

Surface Bursts

Figure 1 shows surface burst data together with scaling relationships developed (Henny and Carlson, Reference 6). The power law for the ballistic boundary for missiles from hemispherical charges on soil parallels the one for hemispherical charges on rock, but its value is about 45 percent of that for rock. In spite of the poorer shock transmission in soil, the shock strengths are sufficient to break the soil into smaller pieces of ejecta which have a more drag-limited trajectory.

The White Tribe boundary is nearly twice that for the SES events (Table IV), either because the caliche tends to form clods which have a greater range or because the charge was one of three detonated simultaneously in a triangular array which may have resulted in an enhanced trajectory.

For spherical charges, the results of the MTCE events yield power laws quite different from those of hemispherical charges (Tables I and III). There is no clear reason why a ballistic boundary from spherical charges should scale differently. It is a judgment that the boundary for the 2000 and 4000-pound spherical charges is too small, either because maximum trajectory missiles were not produced or because, if produced, they were not found. It is also believed that a better description of the ballistic boundary would be given by a power law of

approximately $W^{0.4}$ applied to the maximum range for the 16,000-pound MTCE and the Flat Top I events. This suggests nearly twice the maximum range for spherical charges as for hemispherical.

The 2425-, 3325-, and 3286-foot ranges for the Air Vent I, and Flat Top II and III spherical charges (Table II) are for plastic artificial missiles. They probably represent typical boundaries for soil containing rocks of comparable size.

Buried Charges

Observed ballistic boundaries for buried spherical charges are also tabulated in Tables I and II. Attempts to scale the ballistic boundary by cube-root scaling made it clear that cube-root scaling was not applicable. Trials with other scaling values indicated that the most consistent results could be obtained by scaling the depth of burst (DOB) by $W^{1/3}$ and the maximum ballistic range by $W^{1/6}$. The upper boundary of the DOB/range relationship is in the rock data of Buckboard, Pre-Schooner, Pre-Schooner II, and Palanquin. The Sulky maximum range is low because it was obtained from aerial photographs rather than ground-level observation. For Dugout, a row charge, both the weight of a single charge and of the total row are indicated. If scaled as a single 40,000-pound charge, Dugout is in reasonable agreement with the other rock data (see Figure 2). Palanquin is also shown twice in Figure 2, both for the announced yield and for half that value; the lower yield was indicated by air-blast data (Reference 27).

The maximum values for soil are always less than those for rock because the soil breaks into less than optimum trajectory sizes, the stress wave is weaker, and what stones there are in the soil may not be of a size and location for maximum trajectory. In principle the ballistic boundary for stones included in soil could nearly equal that for rock if a stone of the proper size existed in an appropriate location. The probability is low, however. Maxima from Sedan and from CAPSA 8 approach rock values but the plastic artificial missile of Air Vent I did not do so, and in the same shot, natural missiles were observed only to 1800 feet.

$$\begin{aligned} \text{MAX RANGE soil-hemispherical} &= 14.8 W^{.35} \approx Z W^{.4} \\ Z &= 13.19 \text{ for } W=10^5 \end{aligned}$$

Conclusions

Surface Explosions: $(10^3 \text{ lb to } 10^6 \text{ lb})$

Hemispheres

Spheres

$$\text{Rock} \begin{cases} R_{\max} = 30W^{0.4} \\ R_{\max} = 70W^{0.4} \end{cases}$$

$$\text{Soil} \begin{cases} R_{\max} = 13W^{0.4} \\ R_{\max} = 30W^{0.4} \end{cases}$$

Buried Explosions: $(10^3 \text{ lb to } 0.5 \text{ kt})$

$$R_{\max} = W^{1/6} \left[-533 \left(\frac{\text{DOB}}{W^{1/3}} \right)^3 + 2307 \left(\frac{\text{DOB}}{W^{1/3}} \right)^2 - 3678 \left(\frac{\text{DOB}}{W^{1/3}} \right) + 2407 \right]$$

There is a finite probability that boundaries arrived at on the basis of a small sample would be exceeded by a larger number of events. Where the above relationships are used for safety considerations, it is advisable that the maximum ranges be multiplied by 1.5 or 2.

There is a paradox in that the maximum ranges for surface bursts scale as $W^{0.4}$ whereas those for buried charges appear to scale as $W^{1/6}$. There is a similar paradox related to scaling of crater radius; surface bursts scale as $W^{0.4}$ and buried charges as $W^{1/4-1/3}$. Since we are unable to explain either, it would not be surprising if both paradoxes were found to have a common cause. Both leave an uncertainty about which scaling is proper for shallow buried charges. Thus, in the region between zero and $\frac{\text{DOB}}{W^{1/3}} = 0.4 \text{ ft/lb}^{1/3}$, it is recommended that the surface burst predictions be applied.

$$\text{for } 10^5 \text{ lb: } \frac{\text{MAX RANGE Soil-Hemisphere}}{\text{MAX RANGE Rock-Hemisphere}} = \frac{14.8(10^5)^{.39}}{30.2(10^5)^{.40}} = .4368$$

Assuming:

$$\frac{\text{MAX RANGE Soil-sphere}}{\text{MAX RANGE Rock-sphere}} \approx .4368 \text{ Also, then:}$$

$$\text{MAX RANGE Soil-sphere} \approx .4368 (70W^{0.4}) = 30.58W^{0.4}$$

for Rock:

$$\frac{\text{MAX RANGE spheres}}{\text{MAX RANGE Hemispheres}} = \frac{70W^{0.4}}{30W^{0.4}} = \frac{7}{3}$$

Assuming for soil:

$$\frac{\text{MAX RANGE spheres}}{\text{MAX RANGE Hemispheres}} \approx \frac{7}{3} \text{ also then: MAX RANGE spheres} \approx 14.8 \left(\frac{7}{3} \right) W^{0.39}$$

$$Z = 30.78 \therefore \text{ use } 30.78W^{0.4}$$

$$34.53(10^5)^{.39} = Z(10^5)^{.40}$$

$$\text{but } = 34.53W^{.39}$$

TABLE I
Spherical Charges - Rock Medium

| <u>Series-Shot</u> | <u>Charge Weight</u> | <u>Burial Depth (ft)</u> | <u>Maximum Range (ft)</u> | <u>Medium</u> | <u>Ref</u> |
|--------------------|----------------------|----------------------------------|-----------------------------------|---------------|------------|
| MTCE - ST1 | 4,000 lb | 2.2 above | 250 | Basalt | 6 |
| - ST3a | 4,000 lb | 2.2 above | 180 | Basalt | 6 |
| - S2a | 4,000 lb | 0 | 850 | Basalt | 6 |
| - S4a | 4,000 lb | 0 | 720 | Basalt | 6 |
| - C2 | 4,000 lb | 2.2 | 3,300 | Basalt | 6 |
| - CS | 2,000 lb | 0 | 450 | Basalt | 6 |
| - LS | 16,000 lb | 0 | 3,225 | Basalt | 6 |
| Flat Top I | 40,000 lb | 0 | 4,060 | Limestone | 7 |
| Buckboard 11 | 40,000 lb | 25.5 | 4,158 | Basalt | 8 |
| Buckboard 12 | 40,000 lb | 42.7 | 1,988 | Basalt | 8 |
| Buckboard 13 | 40,000 lb | 58.8 | No Record | Basalt | 8 |
| Buckboard 5, 10 | 1,000 lb | 5 | 3,300 | Basalt | 8 |
| Buckboard 4 | 1,000 lb | 10 | 1,650 | Basalt | 8 |
| Buckboard 8 | 1,000 lb | 15 | 870 | Basalt | 8 |
| Pre-Schooner A | 39,250 lb | 59 | 507 | Basalt | 9 |
| B | 39,450 lb | 51 | 984 | Basalt | 9 |
| C | 39,840 lb | 67 | 216 | Basalt | 9 |
| D | 39,590 lb | 43 | 1,550 | Basalt | 9 |
| Pre-Schooner II | 180,000 lb | 71 | 2,320 | Basalt | 10 |
| Dugout | 5x40,000 lb (Row) | 59 | 1,279 | Basalt | 11 |
| Palanquin | 4.3 kt | 280 | 1,590 | Basalt | 12 |
| Danny Boy | 0.43 kt | 110 | > 879 | Basalt | 13 |
| Sulky | 0.085 kt | 90 | > 87 | Basalt | 14 |

TABLE II
Spherical Charges - Soil

| <u>Series-Shot</u> | <u>Charge Weight</u> | <u>Burial Depth (ft)</u> | <u>Maximum Range (ft)</u> | <u>Medium</u> | <u>Ref</u> |
|--------------------|----------------------|------------------------------|-----------------------------------|-------------------------|------------|
| Sedan | 100 kt | 635 | 7,019 | NTS alluvium | 15 |
| CAPSA 8 | 1,000 lb | 12.5 | 970 | Albuquerque alluvium | 16 |
| Stagecoach 1 | 40,000 lb | 80 | No Record | NTS alluvium | 17 |
| Stagecoach 2 | 40,000 lb | 17.1 | 510 | NTS alluvium | 17 |
| Stagecoach 3 | 40,000 lb | 34.2 | 1,793 | NTS alluvium | 17 |
| Scooter | 1,000,000 lb | 100 | No Record | NTS alluvium | 18 |
| Dugway 310 | 320 lb | 3.5 above | 250 | Dry clay | 19 |
| Dugway 312 | 2,560 lb | 7 | 500 | Dry clay | 19 |
| Dugway 315 | 40,000 lb | 17.5 | 1,050 | Dry clay | 19 |
| Dugway 318 | 320,000 lb | 35 | 3,500 | Dry clay | 19 |
| Air Vent I | 40,000 lb | 17.1 | 1,800/ 2,425* | Playa | 20 |
| Jangle HE 3 | 2,560 lb | 6.84 | 3,500 | NTS alluvium | 21 |
| Jangle U | 1.2 kt | 17 | 5,500 | NTS alluvium | 22 |
| Flat Top II | 40,000 lb | 0 | 3,325* | Playa | 20 |
| Flat Top III | 40,000 lb | 0 | 3,286* | Playa | 20 |

*Plastic artificial missile

TABLE III
Hemispherical Charges - Rock

| <u>Series-Shot</u> | <u>Charge Weight (lb)</u> | <u>Burial Depth (ft)</u> | <u>Maximum Range (ft)</u> | <u>Medium</u> | <u>Ref</u> |
|--------------------|-------------------------------|------------------------------|-----------------------------------|---------------|------------|
| MTCE H1 | 4,000 | 0 | 780 | Basalt | 5 |
| MTCE H2 | 16,000 | 0 | 1,500 | Basalt | 5 |
| Sailor Hat | 1,000,000 | 0 | 7,200 | Basalt | 23 |

TABLE IV
Hemispherical Charges - Soil

| Series-Shot | Charge Weight (lb) | Burial Depth (ft) | Maximum Range (ft) | Medium | Ref |
|---------------|-----------------------|----------------------|--------------------------|---------|-----|
| White Tribe | 11,560 | 0 | 1,100 | Caliche | 24 |
| SES- Snowball | 1,000,000 | 0 | 3,250 | Silt | 25 |
| SES | 200,000 | 0 | 1,850 | Silt | 26 |
| SES | 10,000 | 0 | 540 | Silt | 26 |




Figure 1. Surface burst scaling relationships
(Data for rock from Reference 6)




Figure 2. Buried charges scaling relationships

References

1. "Computer Calculations of Explosion-Produced Craters," UCRL-14998, Cherry, J. T., University of California, Lawrence Radiation Laboratory, July 14, 1966.
2. "The Effect of Air Drag on Particles Ejected During Explosive Cratering," UCRL-14974, Sherwood, A. E., University of California, Lawrence Radiation Laboratory, June 27, 1966.
3. "Throwout Calculations for Explosion Craters," J. Geophys. Res., 66, 3405, Hess, W. N., and Nordyke, M. D., 1961.
4. "Maximum Missile Ranges from Cased Explosive Charges," SC-4205 (TR), Bishop, R. H., Sandia Corporation, Albuquerque, New Mexico, 1958.
5. "The Initial Velocities of Fragments from Bombs, Shells, and Grenades," Ballistics Research Laboratory Report No. 405, Gurney, R. W., Aberdeen Proving Ground, Maryland, September 14, 1943.
6. Multiple Threat Cratering Experiment-Volume III, "Natural Missile Distribution for High Explosive Craters in Hard Rock," AFWL-TR-67-8, Henny, R. W., and Carlson, R. H. To be released about September 1, 1967.
7. Ferris Wheel Series, "Flat Top Event, Crater Measurements," Rooke, A. D., Davis, L. K., U. S. Army Engineer Waterways Experiment Station, Vicksburg, Mississippi, August 9, 1966.
8. Project Buckboard, "20-Ton and 1/2 Ton High Explosive Cratering Experiments in Basalt Rock," Vortman, L. J. (Scientific Advisor) MacDougall, H. R. (Technical Director), et al, SC-4675 (RR), TID-4500, July - September 1960.
9. Project Pre-Schooner, "Crater Measurements, Final Report," PNE-502F, Spruill, J. L., and Paul, R. A., U. S. Army Engineer Nuclear Cratering Group, Livermore, California, March 1965.
10. Pre-Schooner II Preliminary Report, PNE-509, Hughes, B. C., Technical Director's Summary Report, Nuclear Cratering Group.
11. Project Dugout, "Apparent Crater Studies, Final Report," PNE-601F, Spruill, J. L. (Captain), U. S. Army Engineer Nuclear Cratering Group, Livermore, California, March 1965.
12. Project Palanquin, "Studies of the Apparent Crater, Final Report," PNE-904, Videon, F. F., U. S. Army Engineer Nuclear Cratering Group, Livermore, California, July 1966.
13. Project Danny Boy, "Mass Distribution Measurements of Crater Ejecta and Dust," POR-1815 (WT-1815), Rooke, A. D. and Davis, L. K., Waterways Experiment Station, February 13, 1964.

14. Project Sulky, "Crater Measurements," PNE-713F, Videon, F., Nuclear Cratering Group, U. S. Army Corps of Engineers, Livermore, California, October 1965.
15. Project Sedan, "Mass Distribution and Throwout Studies, Final Report," PNE-217F, Carlson, R. H., and Roberts, W. A., The Boeing Company, August 6, 1963.
16. Sandia Corporation, unreported data, Shot CAPSA 8.
17. Project Stagecoach, "20-Ton HE Cratering Experiments in Desert Alluvium," SC-4596 (RR), TID-4500, Vortman, L. J. (Scientific Advisor) and MacDougall, H. R. (Technical Director), et al, May 1962.
18. "Project Scooter," SC-4602 (RR), TID-4500, Perret, W. R., et al, Sandia Laboratory, Albuquerque, New Mexico, October 1963.
19. Underground Explosion Test Program--Final Report, Volume I, "Soil," Engineering Research Associates, Inc., Armour Research Foundation, Rensselaer Polytechnic Institute, August 30, 1952.
20. Ahlers, E. B., IIT Research Institute, Chicago, Illinois, Private Communication.
21. "Scaled HE Tests, Final Report," AFWSP-123, Doll, E. B., and Salmon, V., Stanford Research Institute, December 1952.
22. "Cratering Phenomena, Operation Jangle," WT-373, Bishop, J. A., and Lowance, F. E., May 1952.
23. Project Sailor Hat, "Time History and Pattern of Natural Missile Deposition for a 500-Ton High-Explosive, Surface-Cratering Event in Rock," D2-125039-1, Knoll, J. A., The Boeing Company, Seattle, Washington, May 15, 1967.
24. Local Distribution of Material Ejected by Surface Explosions: White Tribe Interim Report, D2-6955-2, Carlson, R. H., and Roberts, W. A., The Boeing Company, August 1961.
25. "Distribution of Natural Missiles Resulting from Cratering Explosions in Hard Rock," Henny, R. W. (Air Force Weapons Laboratory) and Carlson, R. H. (The Boeing Company), Proceedings of the Conference on Prevention of and Protection Against Accidental Explosion of Munitions, Fuels and Other Hazardous Mixtures in New York City, October 13, 1966. To be published.
26. "Ejecta Study of 100-Ton Suffield Explosive Cratering Shot," D2-90203, Carlson, R. H., et al, The Boeing Company, October 8, 1962.
27. "Project Palanquin, Close-in Air Blast from a Cratering Nuclear Detonation in Phylolite," PNE-902F, Vortman, L. J., Sandia Corporation, Albuquerque, New Mexico, April 1966.

DISTRIBUTION:
TID-4500, UC-35 plus UC-41 (406 copies)

Brig. Gen. D. L. Crowson
AEC/Div. of Military Application
Washington, D. C.

U. S. Atomic Energy Commission
Dept. Peaceful Nuclear Explosives
Washington, D. C.
Attn: J. S. Kelly, Director (25)
Richard Hamburger (1)
William Oakley (1)

E. L. Brawley
Industrial Safety Branch
U. S. Atomic Energy Commission
Albuquerque Operations Office
Albuquerque, New Mexico 87115

John Philip
AEC/San Francisco Operations Office
Berkeley, California (5)

G. M. Dunning
AEC/Division of Health and Safety
Washington 25, D. C.

Mr. R. Perkins
Armed Forces Explosive Safety
Board
Washington, D. C. 20315

P. W. Ager, AEC/SAO

D. W. King, AEC/ALO (2)

U. S. Atomic Energy Commission
Nevada Operations Office
P. O. Box 1676
Las Vegas, Nevada 89101
Attn: G. B. Maxey, Consultant (1)
T. F. Thompson, Consultant (1)
Arnold Sparin, Ind. Safety
Branch (1)

John Rinehardt
ESSA/IER
Boulder, Colorado 80302

F. L. Smith
Colorado School of Mines
Golden, Colorado

E. M. Purcell
Harvard University
Cambridge, Massachusetts

Charles W. Martin
201 T and AM Lab
Iowa State University
Ames, Iowa

Robert V. Whitman
Massachusetts Institute of
Technology
Cambridge, Massachusetts

N. M. Newmark
University of Illinois
Urbana, Illinois

M. A. Cook
Explosives Research Group
University of Utah
Salt Lake City, Utah

Eugene M. Shoemaker, Chief
Branch of Astrogeology
Geologic Division
U. S. Geologic Survey
P. O. Box 1906
Flagstaff, Arizona

Ralph B. Baldwin
1745 Alexander Rd., SE
East Grand Rapids, Michigan

J. J. Gilvarray
Research Laboratories
Allis-Chalmers Manufacturing Co.
Milwaukee, Wisconsin

R. H. Carlson
Boeing Airplane Company
Suite 1707
First National Bank Building
Albuquerque, New Mexico

John F. Ridosko
SWSS-1
Kirtland Air Force Base
Albuquerque, New Mexico 87117

U. S. Army Ballistic Research Lab.
Aberdeen Proving Ground,
Maryland 21005
Attn: C. W. Lampson (1)
J. J. Meszaros (1)

J. G. Lewis/J. Kelso
Hq/DASA
Washington 25, D. C.

Paul Russell
Bureau of Mines
Washington, D. C.

William Hardwick
Bureau of Mines
Tucson, Arizona

J. C. Mark, LASL

W. E. Ogle, LASL

Roy Reider
H3 Safety Office
Los Alamos Scientific Laboratory
Los Alamos, New Mexico

University of California
Lawrence Radiation Laboratory
P. O. Box 808
Livermore, California 94551
Attn: M. M. May/D. Sewell (1)
G. C. Werth (1)
G. H. Higgins (10)
M. D. Nordyke (1)
W. Slazak, NCG (1)
Evo Bernadini (1)

T. Schiffman
Illinois Institute of Technology
Research Institute
Chicago, Illinois

Office, Chief of Engineers
Department of the Army
Washington, D. C. 20315
Attn: R. W. Beene (1)
J. A. Hughes (1)
M. D. Kirkpatrick (1)

W. E. Clark
Oak Ridge National Laboratory
Oak Ridge, Tennessee

RAND Corporation
1700 Main Street
Santa Monica, California
Attn: D. T. Griggs (1)
H. L. Brode (1)

Stanford Research Institute
P. O. Box 725
Menlo Park, California 94025
Attn: R. B. Vaile (1)
Carl K. Wiehle (1)

A. Brown
U. S. Geological Survey
Room 1033, GSA Building
Washington 25, D. C.

Fred Houser
U. S. Geological Survey
Denver Federal Center
Denver, Colorado

Herman Phillips
Mason and Hanger - Silas Mason Co.
P. O. Box 647
Amarillo, Texas 79105

J. A. Hornbeck, 1
L. M. Jercinovic, 3210
D. L. Rost, 3211
H. S. North, 3211
E. F. Armbrust, 3211
R. C. Fletcher, 5000
R. S. Claassen, 5100
T. B. Cook, 5200
C. R. Mehl, 5230
J. D. Shreve, 5234
J. W. Weihe, 5250
R. A. Bice, 7000
B. F. Murphey, 7100
C. D. Broyles, 7110
L. J. Vortman, 7111
M. L. Merritt, 7111 (5 DPNE)
M. L. Merritt, 7111 (25)
J. W. Reed, 7111
G. E. Hansche, 7120
C. S. Selvage, 7130
R. K. Peterson, 7132 (3)
R. D. Statler, 7133 (3)
L. E. Hollingsworth, 7200
S. A. Moore, 7230
A. J. Max, 7233
B. C. Benjamin, 7242
W. E. Holder, 7262
M. McWhirter, 7340
F. H. Mathews, 7343
F. J. Murar, 8125
B. F. Hefley, 8232
G. L. Rhodes, 8255
J. G. Marsh, 3414
B. R. Allen, 3421
L. C. Baldwin, 3412
R. S. Gillespie, 3413 (2)
For: H. F. Carroll, USAEC
C. H. Sproul, 3428-2 (2)